

VERIFICATION

The undersigned, of the below address, hereby certifies that he/she well knows both the English and Japanese languages, and that the attached is an accurate English translation of the Japanese Patent application filed on June 21, 2002 under No. P2002-181821.

The undersigned declares further that all statements made herein of his/her own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Signed this 9th day of April, 2007.

Signature:

A handwritten signature in black ink, appearing to be "Shiro Terasaki".

Name: Shiro TERASAKI

Address: c/o Soei Patent & Law Firm Ginza First Bldg.,  
10-6, Ginza 1-chome, Chuo-ku, Tokyo 104-0061  
Japan

[Document Name] Specification

[Title of the Invention] FIBER LASER UNIT

[Claims]

[Claim 1] Fiber laser unit comprising a  
5 plurality of fiber lasers that generate laser beams  
by exciting a laser active substance inside cores by  
exciting light, propagate the laser beams inside the  
cores and output from the ends thereof, wherein

each of the fiber lasers has a resonator structure  
10 that reflects a laser beam on both ends, and

the cores of the fiber lasers are made proximal  
to each other at a part, and by using a laser beam  
outputted from the inside of the core of an arbitrary  
fiber laser, injection synchronization is carried out  
15 inside resonators of other fiber lasers.

[Claim 2] The fiber laser unit according  
to Claim 1, wherein

each of the fiber lasers has a structure in which  
a part of the cores is reduced in diameter, and the  
20 cores are made proximal to each other at the core  
diameter reduced portion.

[Claim 3] The fiber laser unit according  
to Claim 2, wherein the diameter reduced portion and  
the proximity portion are formed by an optical fiber  
25 coupler.

[Claim 4] The fiber laser unit according

to any one of Claims 1 through 3, wherein, among the plurality of fiber lasers, a loss is applied to ports of the fiber lasers except for one fiber laser.

5 [Detailed Description of the Invention]

[0001]

[Technical Field to which the Invention Pertains]

The present invention relates to a fiber laser unit having a plurality of fiber lasers.

10 [0002]

[Prior Art]

Various lasers have been actively developed, and in particular, among the lasers, a laser with high output and high spatial coherence has been demanded.

15 As a method for realizing this, there is known a method which realizes high output by coherent addition (coupling) of outputs of a plurality of lasers. As an example, coherent addition (coupling) of lasers by means of evanescent coupling of laser arrays or  
20 diffraction coupling by using a Talbot mirror have been studied. An example of the evanescent coupling is disclosed in "Diode Laser Arrays," Cambridge Publication, and an example of the Talbot resonator is disclosed in "Laser Engineering," society magazine  
25 of the Laser Society of Japan.

[0003]

[Problem to be Solved by the Invention]

However, as described above, in the coherent addition of the conventional method, various super modes are easily excited as well as a super mode to  
5 be coherently added. Furthermore, a distant field image coherently added also has fringe corresponding to the spatial frequencies of the laser arrays and its beam pattern is inferior. Therefore, in the conventional method, an increase in loss caused by  
10 these poses various problems such that high addition efficiency cannot be obtained, and practical use thereof has not been realized. Particularly, in the case of a Talbot resonator, very accurate adjustment is required so as to obtain phase coupling, so that  
15 it is not suitable for industrial use.

[0004]

Therefore, an object of the present invention is to provide a fiber laser unit excellent in addition efficiency of coherent addition.

20 [0005]

[Means for Solving the Problem]

A fiber laser unit relating to the present invention has a plurality of fiber lasers that generate laser beams by exciting a laser active substance inside  
25 cores by exciting light and propagate the laser beams in the cores and output them from the end portions,

wherein each fiber laser has a resonator structure that reflects a laser beam on both ends, the cores of the fiber lasers are made proximal to each other at a part, and by a laser beam that has excited from the inside  
5 of the core of an arbitrary fiber laser, injection synchronization is carried out inside the resonators of other fiber lasers.

[0006]

According to this fiber laser unit, laser beams  
10 leak from the cores of the respective fiber lasers, and the leaked laser beams enter the cores of other fiber lasers disposed in proximity and are coupled with the laser beams propagating inside the cores of the other fiber lasers, and injection synchronization is  
15 carried out inside the resonators. At this point, when the fiber lasers are structured so that a laser beam is outputted from one fiber laser among the plurality of fiber lasers, laser beams are coherently added with high addition efficiency inside the resonator of the  
20 one fiber laser, and from the end portion thereof, a coherently added laser beam is outputted.

[0007]

In the above-described fiber laser unit of the present invention, it is also possible that the cores  
25 of the fiber lasers are reduced in diameter at a part and the diameter reduced portions of the cores are made

proximal to each other.

[0008]

According to this fiber laser unit, a large amount of laser beams leak due to reduction in diameter of the cores and promotes injection synchronization.

[0009]

In the fiber laser unit of the present invention, it is possible that the diameter reduced portion and the proximity portion are formed by an optical fiber coupler.

[0010]

According to this fiber laser unit, the section where the cores are reduced in diameter and made proximal to each other is formed by an optical fiber coupler, whereby the entire unit can be easily constructed.

[0011]

In the fiber laser unit of the present invention, it is possible that, among the plurality of fiber lasers, except for one fiber laser, a loss is applied to ports of other fiber lasers.

[0012]

According to this fiber laser unit, by applying a loss such as a bend loss to the ports of fiber lasers except for one fiber laser, a fiber laser to output a coherently added laser beam can be specified.

Thereby, the output port can be switched in the fiber laser unit.

[0013]

[Embodiments of the Invention]

5 Hereinafter, an embodiment of a fiber laser unit of the present invention is described with reference to the drawings.

[0014]

10 In the invention, for realizing coherent addition with high addition efficiency, a fiber laser unit is constructed in which a part of the cores of a plurality of fiber lasers is reduced in diameter to leak laser beams from cores, the leaked laser beams are made to enter the insides of the cores of other fiber lasers  
15 disposed in proximity to carry out injection synchronization. When this fiber laser unit is formed so that a laser beam is outputted from one fiber laser by means of application of a bend loss, etc., to ports, from the one fiber laser, an output coherently added  
20 with laser beams of other fiber lasers is obtained.

[0015]

In this embodiment, the concept of the invention is described and then a fiber laser unit having two fiber lasers applied with the invention is described  
25 in detail. In this embodiment, the structure of the portion where the cores are made proximal to each other

and reduced in diameter is also described with two patterns.

[0016]

The concept of the fiber laser unit relating to the invention is described with reference to Fig. 1 and Fig. 2. Fig. 1 is a conceptional view of the fiber laser unit relating to the invention. Fig. 2 is a schematic view of coherent addition in a fiber laser unit having N fiber lasers relating to the invention.

[0017]

The fiber laser unit 1 has two fiber lasers 2 and 3. The fiber lasers 2 and 3 are single mode fiber lasers with cores 2a and 3a doped with a laser active substance such as erbium (Er), etc., which form resonators 4 and 5 having one end portions 2b and 3b that fully reflect laser beams and the other end portions 2c and 3c that partially reflect laser beams. The fiber lasers 2 and 3 are formed so that the cores 2a and 3a are thin at the middle portions 2d and 3d thereof. In the fiber laser unit 1, the middle portions 2d and 3d where the cores 2a and 3a are reduced in diameter are disposed in proximity to each other. The level of this proximity corresponds to oscillation wavelengths of laser beams (several micrometers). In the fiber laser unit 1, the output sides from the middle portions 2d and 3d (when they are formed by an optical



fiber coupler, the output side from the optical fiber coupler) serve as ports of fiber lasers 2 and 3.

[0018]

In the fiber laser unit 1, when the cores 2a and  
5 3a of the fiber lasers 2 and 3 are irradiated with  
exciting light, the laser active substance is excited  
to cause laser oscillation, and laser beams with  
oscillation wavelengths different from each other are  
generated. At this point, in this fiber laser unit  
10 1, the cores 2a and 3a are reduced in diameter at the  
middle portions 2d and 3d of the fiber lasers 2 and  
3, a large amount of laser beams leak from there. Then,  
a part of the leaked laser beams enters the cores 2a  
and 3a of the other fiber lasers 2 and 3 and are coupled  
15 with laser beams generated in the cores 2a and 3a that  
the leaked laser beams have entered to carry out  
injection synchronization inside the resonators 4 and  
5. At this point, when a loss is applied to the port  
of either one of the fiber lasers 2 and 3, a coherently  
20 added laser beam is outputted from the other ends 2c  
or 3c of the other fiber laser 2 or 3 that has not been  
applied with the loss. This coherently added output  
becomes almost equal to a sum of output values of the  
laser beams when the fiber lasers 2 and 3 output the  
25 laser beams independently.

[0019]

Furthermore, leak of laser beams is promoted by reducing the diameters of the cores 2a and 3a, and even when the cores 2a and 3a are not reduced in diameter, laser beams leak from the cores 2a and 3a, so that the  
5 cores 2a and 3a are not necessarily reduced in diameter. The most important point is that the cores 2a and 3a are disposed in proximity to each other. As the distance between the cores 2a and 3a becomes shorter, the near-field interaction becomes greater and the  
10 section of proximity of the cores 2a and 3a can be shortened (when this section is formed by an optical fiber coupler, the length of the optical fiber coupler can be shortened). On the other hand, even when the distance between the cores 2a and 3a is long, the same  
15 effect can be obtained by lengthening the section of proximity of the cores 2a and 3a.

[0020]

Coherent addition based on the principle described above can be realized regardless of the  
20 number of fiber lasers. As shown in Fig. 2, in a fiber laser unit 11 having N fiber lasers 12..., the fiber lasers 12... have the same structure as that of the fiber lasers 2 and 3 described above, and an output value when the fiber lasers 12... output laser beams independently is  
25 defined as P. In this fiber laser unit 11, when a loss is applied to the ports of the fiber lasers 12... except

for one fiber laser, an output of  $N \times P$  can be obtained from the one fiber laser 12 that has not been applied with the loss (however, in actuality, the output lowers by several percent due to the loss).

5 [0021]

The structure of a fiber laser unit 21 relating to this embodiment is described with reference to Fig. 3. Fig. 3 is a structural view of the fiber laser unit relating to this embodiment.

10 [0022]

The fiber laser unit 21 has two fiber lasers 22 and 23, and an output obtained by coherent addition of laser beams of the two fiber lasers 22 and 23 can be outputted from one of the fiber lasers. In the fiber laser unit 21, in order to couple the two fiber lasers 22 and 23, an optical fiber coupler 28 is provided on the middle portions 22d and 23d thereof, and coherent coupling of the laser beams between the two fiber lasers 22 and 23 is realized by this optical fiber coupler 28.

20

[0023]

The fiber laser 22 is a single mode fiber laser formed by doping erbium into the core of a silica-based single mode optical fiber 22e, and the entire optical fiber 22e forms a resonator 24 and introduces exciting light by a WDM (Wavelength Division Multiplexing)

25

coupler 26. The fiber laser 22 outputs a laser beam with an oscillation wavelength of 1556.9nm from the port A of the other end portion 22c, and when it outputs independently in a non-coupled state, the output value becomes 1.36W. Furthermore, the fiber laser 22 has a polarization controller 30 on one end portion 22b side to obtain high addition efficiency by equalizing polarization between the lasers. Furthermore, in coherent addition, high addition efficiency cannot be obtained due to interference of a plurality of electric fields unless polarization is equal between lasers, so that a polarization controller 30 is used in the fiber laser unit 21, and the polarization controller can be provided in the fiber laser 23 in place of the fiber laser 22. Furthermore, when a fiber that stores polarization is used, the polarization controller 30 becomes unnecessary.

[0024]

The resonator 24 is formed by a fiber diffraction grating (FBG: Fiber Bragg Grating) 24a provided on one end portion 22b of the fiber laser 22 and a reflecting end face 24b provided on the other end portion 22c. The fiber diffraction grating 24a has characteristics to reflect light with a wavelength of 1556.9nm at a reflectance higher than 99% (almost 100% reflectance), and transmits light with other wavelengths. The

reflecting end face 24b has characteristics to reflect light with a wavelength of 1556.9nm at a reflectance of 3.4% and transmits the remaining light.

[0025]

5           The WDM coupler 26 couples exciting light with 1484nm and 2.05W with the core inside the resonator 24.

[0026]

10           The fiber laser 23 is a single mode fiber laser formed by doping erbium into the core of a silica-based single mode optical fiber 23e, and the entire optical fiber 23e forms a resonator 25 and introduces exciting light by a WDM coupler 27. The fiber laser 23 outputs a laser beam with an oscillation wavelength of 1557.1nm  
15           from the port B on the other end 23c, and when it outputs independently in a non-coupled state, the output value becomes 1.47W.

[0027]

20           The resonator 25 is formed by a fiber diffraction grating (FBG) 25a provided on one end 23b of the fiber laser 23 and a reflecting end face 25b provided on the other end 23c. The fiber diffraction grating 25a has characteristics to reflect light with a wavelength of 1557.1nm at a reflectance higher than 99% (almost 100%  
25           reflectance), and transmits light with other wavelengths. The reflecting end face 25b has

characteristics to reflect light with a wavelength of 1557.1nm at a reflectance of 3.4% and transmits the remaining light.

[0028]

5           The WDM coupler 27 couples exciting light with 1484nm and 2.05W with the core inside the resonator 25.

[0029]

10           The optical fiber coupler 28 is described with reference to Fig. 4 also. Fig. 4 is the optical fiber coupler of Fig. 3, (a) is a side view of the optical fiber coupler, (b) is a plan view of a melt-drawn portion of the optical fiber coupler, (c) is a sectional view along the I-I line of (b).

15           [0030]

20           The optical fiber coupler 28 is of  $2 \times 2$  and has a branching ratio of 50 : 50, wherein laser beams are leaked from cores 22a and 23a of two optical fibers 22e and 23e, and the leaked laser beams are coupled inside the other side cores 22a and 23a. Therefore, the optical fiber coupler 28 has a melt-drawn portion 28a that is formed by melting and drawing the middle portions 22d and 23d of two optical fibers 22e and 23e and joining clads 22f and 23f of the two optical fibers 22e and 23e. At the melt-drawn portion 28a, the optical fibers 22e and 23e (cores 22a and 23a) are reduced in

25

diameter and the cores 22a and 23a are disposed in extremely close proximity to each other.

[0031]

5 In the optical fiber coupler 28, the melt-drawn portion 28a is fixed onto a silica-based substrate 28b and sealed within a space with a small thermal expansion coefficient formed by invar 28c and 28c and sealing materials 28d and 28d.

[0032]

10 Furthermore, in the fiber laser unit 21, in order to output a coherently added laser beam from one of the fiber lasers 22 and 23, a loss is applied to the port of the other one of the optical fibers 22e and 23e. Therefore, in the fiber laser unit 21, in order  
15 to positively increase the bend loss on the port of one of the optical fibers 22e and 23e, the port of one of the optical fibers 22e and 23e is provided with a bend loss portion 29 and the number of times of bending on the port of one of the optical fibers 22e and 23e  
20 is increased to forcibly increase the bend loss. In Fig. 3, the bend loss of the port of the optical fiber 23e is increased, so that a coherently added laser beam is outputted from port A of the fiber laser 22.

[0033]

25 Action of the fiber laser unit 21 is described with reference to Fig. 5 also. Fig. 5 is a diagram

showing output spectra of the fiber laser unit.

[0034]

In the fiber laser unit 21, when exciting light beams are coupled to the cores 22a and 23a of the optical fibers 22e and 23e from the WDM couplers 26 and 27, erbium ions inside the core 22a and 23a are excited and the emitted fluorescence propagates back and forth within the resonators 24 and 25. Then, they are subjected to laser amplification inside the resonators 24 and 25 to generate laser beams with oscillation wavelengths different from each other (1556.9nm and 1557.1nm) inside the resonators 24 and 25, respectively, and the laser beams propagate inside the cores 22a and 23a.

15 [0035]

At this point, since the cores 22a and 23a are reduced in diameter at the melt-drawn portion 28a of the optical fiber coupler 28, laser beams leak from the cores 22a and 23a. Furthermore, since one optical fiber 23e is applied with a loss by means of bending at the bend loss portion 29, at the melt-drawn portion 28a of the optical fiber coupler 28, the laser beam that has leaked from the core 23a is drawn into the core 22a disposed in proximity, and the drawn-in laser beam propagates in the core 22a. Then, while the drawn-in laser beam propagates back and forth inside



the resonator 24, it is coherently coupled with the laser beam that has been generated in the resonator 24 and propagated in the core 22a and the phases are synchronized(injection synchronization). Then, only this coherently coupled (added) laser beam permeates the reflecting end face 24b and is outputted from port A.

[0036]

The coherently added laser beam outputted from port A has an output value of 2.57W, which is almost twice the value obtained when the respective fiber lasers 22 and 23 output independently (port A: 1.36W, port B: 1.47W). Furthermore, as shown in Fig. 5, when the respective fiber lasers 22 and 23 output laser beams independently, the output spectra differ from each other according to the wavelength characteristics of the respective resonators 24 and 25, however, in the case of the output obtained by coherent coupling, its output spectrum shows a single peak at approximately 1557.05nm that is the middle wavelength of the oscillation wavelengths of the fiber lasers 22 and 23. By comparison, when coherently coupling, a laser beam outputted from port B has an output value of 0.17W, and is an output spectrum showing a single peak at approximately 1557.05nm that is the middle wavelength similar to the output spectrum from port A. In this

case, the addition efficiency of the coherent addition is 91% that is sufficiently practicable. In Fig. 5, the horizontal axis indicates wavelength (nm) and the vertical axis indicates optical output (W/nm), the solid line indicates the output spectrum from port A, the dashed line indicates the output spectrum from port B, the thick line indicates the output spectrum in the case of coherent coupling, and the thin line indicates the output spectrum when the fiber lasers output independently from each other.

[0037]

The coupling principle and the loss to be applied in the fiber laser unit 21 are described further with reference to Fig. 6 and Fig. 7. Fig. 6 is a drawing showing an output pattern in a Y mode, (a) is an output pattern in a Y mode when it is outputted from port A, (b) is an output pattern in a Y mode when it is outputted from port B. Fig. 7 shows changes in output at port A and port B when the bend loss to be applied to port A is changed in the fiber laser unit.

[0038]

In the fiber laser unit 21, when two fiber lasers 22 and 23 are completely balanced in resonator length and fiber propagation constant, according to the super mode theory, diagonalization to two modes where outputs are equivalent and only relative phases are different

between port A and port B is obtained. However, in an unbalanced state where the resonator lengths are different from each other, etc., as shown in Fig. 6, in the fiber laser unit 21, due to the drawing-in effect, etc., outputs concentrate on only one port, and diagonalization to two Y modes which outputs are centered on the respective ports. In other words, by making the two ports A and B unbalanced in loss, thresholds of the two Y modes can be made different from each other, and a Y mode of a port with a smaller loss is selectively excited.

[0039]

Therefore, in the fiber laser unit 21, in order to provide a difference between thresholds of the two Y modes and selectively excite either Y mode, the bend loss of one port is forcibly increased. In Fig. 7, the horizontal axis indicates bend loss (%), the vertical axis indicates output from port (W), and outputs of port A and port B when the bend loss of the port A side is changed in the case where the bend loss of the port B side is 9% is shown. When the bend loss to be applied to the port A side is smaller than 9%, a coherently added laser beam is outputted from port A in the fiber laser unit 21. On the other hand, when the bend loss to be applied to the port A side is larger than 9%, in the fiber laser unit 21, a coherently added

laser beam is outputted from port B. When the bend loss to be applied to the port A side is approximately 9%, in the fiber laser unit 21, the bend loss becomes almost equal between the port A side and the port B side and laser beams equivalent to each other are outputted from port A and port B. Therefore, in the fiber laser unit 21, switching of the output ports is realized by applying losses to the ports of the optical fibers 22e and 23e.

10 [0040]

Furthermore, the reason why high addition efficiency is obtained by coherent addition of the laser beams by using fiber lasers is described a somewhat more. In fiber lasers, since the resonator lengths are as long as approximately 10m and the vertical mode interval is only approximately 10MHz, is approximately equal with Locking Range of the injection synchronization, a little difference of the vertical modes between fiber lasers is compensated.

20 Therefore, in spite of the fiber lasers of the multi vertical mode, it is considered that high addition efficiency is realized. Furthermore, the perfect controllability of the horizontal mode, high density and high gain of the vertical mode interval by the long resonator length that is the feature of fiber lasers is also considered as contributing to obtain the

25

nonconventional high addition efficiency.

[0041]

According to this fiber laser unit 21, coherent addition of laser beams is realized by a simple structure in which the cores 22a and 23a are reduced in diameter and disposed in proximity to each other by the optical fiber coupler 28 and a loss is only applied to the port of one of the optical fibers 22e and 23e, whereby the addition efficiency is very high. In addition, in this fiber laser unit 21, switching of the output ports is realized by applying a loss to the port of one of the optical fibers 22e and 23e. Furthermore, in this fiber laser unit 21, by using a laser beam that has leaked from the core of one fiber, injection synchronization into the resonator of the other fiber is carried out, so that accurate adjustment is not necessary so as to obtain phase coupling.

[0042]

Fiber laser unit 31 in which the portion where the cores are reduced in diameter and made proximal to each other is formed by an integral type fiber coupler is described with reference to Fig. 8. Fig. 8 is a schematic view in a case where the portion where the cores are reduced in diameter and made proximal to each other is formed by an integral type fiber coupler.

[0043]

The fiber laser unit 31 has eight fiber lasers 32 through 39, and can output an output obtained by coherent addition of laser beams from the eight fiber lasers 32 through 39 from one fiber laser. Therefore,  
5 an optical fiber coupler 40 is provided in the fiber laser unit 31, and laser beams are coherently coupled among the eight fiber lasers 32 through 39 by the optical fiber coupler 40. The eight fiber lasers 32 through 39 have the same structure as that of the fiber lasers  
10 22 and 23 described above. Laser beam oscillation wavelengths of the fiber lasers 32 through 39 may be different from each other, however, oscillation bands of the resonators must overlap each other.

[0044]

15 The optical fiber coupler 40 is of 8 x 8 and has an equally branching ratio, and has a function which leaks laser beams from the cores of the eight optical fibers 32e through 39e and couples the leaked laser beams inside other cores. Therefore, the optical  
20 fiber coupler 40 has a melt-drawn portion which is formed by melting and drawing eight optical fibers 32e through 39e and joining clads of the eight optical fibers 32e through 39e to each other. At the melt-drawn portion, the eight optical fibers 32e through 39e  
25 (cores) are reduced in diameter and are disposed extremely close to each other.

[0045]

Furthermore, in order to output a coherently added laser beam from one fiber laser, the fiber laser unit 31 applies a loss to the other seven optical fibers.

5 In the example of Fig. 8, in order to output from the fiber laser 35, the other seven optical fibers 32e through 34e and 36e through 39e are applied with a loss. With this structure, in the fiber laser unit 31, a laser output that is slightly less than 8 times the outputs  
10 independently outputted from the respective fiber lasers 32 through 39 is obtained from the fiber laser 35.

[0046]

According to the fiber laser unit 31, by a simple  
15 structure in which the eight fiber lasers 32 through 39 are coupled by the optical fiber coupler 40 of  $8 \times 8$ , a high laser output can be obtained with high addition efficiency. In this example, the structure in which a laser output of slightly less than 8 times  
20 is obtained by the optical fiber coupler 40 of  $8 \times 8$ , however, the number to be coupled is not limited to this, and it is possible that a laser output of slightly less than N times is obtained by an optical fiber coupler of  $N \times N$ .

25 [0047]

Fiber laser unit 51 in which the portion for

reducing the diameters of the cores and making the cores proximal to each other is formed by cascade connection is described with reference to Fig. 9. Fig. 9 is a schematic view of a case where the portion for reducing the diameters of the cores and making the cores proximal to each other is formed by cascade connection.

[0048]

The fiber laser 51 has eight fiber lasers 52 through 59, and can output an output obtained by coherently adding laser beams of the eight fiber lasers 52 through 59 from one fiber laser. Therefore, in the fiber laser unit 51, as a first stage, fiber lasers 52 through 59 are coupled two each by four optical fiber couplers 60 through 63 of  $2 \times 2$ . Furthermore, in the fiber laser unit 51, as a second stage, four fiber lasers 53, 54, 57, and 58 that output coherently added laser beams are coupled two each by two optical fiber couplers 64 and 65 of  $2 \times 2$ . Furthermore, in the fiber laser unit 51, as a third stage, the two fiber lasers 54 and 57 that output coherent added laser beams are coupled by one optical fiber coupler 66 of  $2 \times 2$ . The eight fiber lasers 52 through 59 have the same structure as that of the fiber lasers 22 and 23 described above. The oscillation wavelengths of the laser beams of the fiber lasers 52 through 59 may be different from each other, however, the oscillation bands of the resonators



must overlap each other. The optical fiber couplers 60 through 66 have the same structure as that of the optical fiber coupler 28 described above.

[0049]

5           Furthermore, in order to output a coherently added laser beam from one fiber laser, the fiber laser unit 51 applies losses to the other seven optical fibers in a phased manner. In the example of Fig. 9, first, in the first stage, in order to output from the fiber  
10           lasers 53, 54, 57, and 58, the other four optical fibers 52e, 55e, 56e, and 59e are applied with a loss, and furthermore, in the second stage, in order to output from the fiber lasers 54 and 57, another two optical fibers 53e and 58e are applied with a loss, and in the  
15           third stage, in order to output from the fiber laser 54, the other one optical fiber 57e is applied with a loss. With this structure, in the fiber laser unit 51, a laser output of slightly less than 8 times the outputs outputted independently from the fiber lasers  
20           52 through 59 is obtained from the fiber laser 54.

[0050]

          According to the fiber laser unit 51, by cascade connection by using seven optical fiber couplers 60 through 66 of  $2 \times 2$ , coherent coupling of eight fiber  
25           lasers 52 through 59 is realized and a high laser output is obtained with high addition efficiency. In this

example, the structure in which eight fiber lasers 52 through 59 are coherently coupled by seven optical fiber couplers 60 through 66 of  $2 \times 2$  is described, however, the number of fiber lasers are not limited to this, and coherent addition can be realized in a larger number of stages with a simple structure. Furthermore, it is also possible that coherent addition is realized in many stages by means of cascade connection by using optical fiber couplers of  $4 \times 4$  and  $3 \times 3$ .

[0051]

An embodiment relating to the invention is described above, however, the present invention is not limited to the embodiment described above and can be carried out in various modes.

[0052]

For example, in the embodiment, a structure is described in which the fiber laser unit is provided with two fiber lasers, however, the same action and effect is obtained even by a fiber laser unit provided with three or more fiber lasers, and it becomes possible to obtain a laser beam with a higher output by a larger number of fiber lasers.

[0053]

Furthermore, a bend loss is applied as a loss in the present embodiment, however, a loss may be

applied by other means such as immersion with index-matching liquid on the end face.

[0054]

Furthermore, in the present embodiment, an optical fiber coupler is used for the core diameter reduced portion, an FBG is used as a resonator, and a WDM coupler, etc., is used for introduction of exciting light, however, they are not limited to these, and these parts may be formed by other means. Particularly, for the core diameter reduced portion, an optical fiber coupler is not necessarily used, and any device can be used as long as it serves as a beam splitter.

[0055]

Furthermore, in the present embodiment, erbium is used as a laser active substance, however, other rare-earth elements, etc., can be used.

[0056]

In addition, in the present embodiment, the oscillation wavelengths of laser beams of the two fiber lasers are set to different wavelengths (1556.9nm and 1557.1nm), however, they may be set to the same wavelength. In the case of the different wavelengths, the oscillation bands of the resonators must overlap each other.

[0057]

[Effects of the Invention]

A fiber laser unit relating to the invention can realize coherent addition of lasers with extremely high addition efficiency by a simple structure in which  
5 injection synchronization is carried out by laser beams leaked from cores by making the cores proximal to each other. Furthermore, this fiber laser unit does not need accurate adjustment to obtain phase coupling since, by using a laser beam leaked from one core,  
10 injection synchronization into the resonator of another fiber laser is carried out. Therefore, this fiber laser unit can be widely practicable for industrial use.

[0058]

15 Furthermore, the fiber laser unit relating to the present invention forms the portion where the cores are reduced in diameter and made proximal to each other by an optical fiber coupler, whereby the entire unit can be easily structured. In addition, the fiber laser  
20 unit relating to the present invention can control the output destination and make switching by applying a loss to the ports of fiber lasers other than a fiber laser that is made to output.

[Brief Description of the Drawings]

25 [Fig. 1]

Fig. 1 is a conceptional view of a fiber laser

unit relating to the present invention.

[Fig. 2]

Fig. 2 is a schematic view of coherent addition in fiber laser unit having N fiber lasers relating to the present invention.

[Fig. 3]

Fig. 3 is a structural view of a fiber laser unit relating to an embodiment of the present invention.

[Fig. 4]

Fig. 4 is the optical fiber coupler of Fig. 3, (a) is a side view of the optical fiber coupler, (b) is a plan view of a melt-drawn portion of the optical fiber coupler, (c) is a sectional view along the I-I line of (b).

[Fig. 5]

Fig. 5 is a diagram showing output spectra of the fiber laser unit of Fig. 3.

[Fig. 6]

Fig. 6 is a drawing showing an output pattern in a Y mode, (a) is an output pattern in a Y mode when it is outputted from port A, (b) is an output pattern in a Y mode when it is outputted from port B.

[Fig. 7]

Fig. 7 is a diagram showing changes in output of the port A and the port B when a loss to be applied to the port A is changed in the fiber laser unit of

Fig. 3.

[Fig. 8]

Fig. 8 is a schematic view of a fiber laser unit relating to the present invention in which a portion where the cores are reduced in diameter and made proximal to each other is formed by an integral type fiber coupler.

[Fig. 9]

Fig. 9 is a schematic view of a case where the portion where the cores are reduced in diameter and made proximal to each other is formed by cascade connection.

[Explanation of Reference Numerals]

1,11,21,31,51...fiber laser unit  
2,3,12,22,23,32~39,52~59...fiber laser  
2a,3a,22a,23a...core  
2b,3b,22b,23b...one end portion  
2c,3c,22c,23c...other end portion  
2d,3d,22d,23d...middle portion  
22e,23e,32e~39e,52e~59e...optical fiber  
22f,23f...clad  
4,5,24,25...resonator  
24a,25a...fiber diffraction grating  
24b,25b...reflecting end face  
26,27...WDM coupler  
28,40,60~66...optical fiber coupler

28a...melt-drawn portion

28b...substrate

28c...invar

28d...sealing material

5 29...bend loss portion

30...polarization controller

[Document Name] ABSTRACT

[Abstract]

[Problem] An object of the present invention is to provide a fiber laser unit excellent in addition efficiency of coherent addition.


[Means of Solution] Fiber laser unit 1 comprises a plurality of fiber lasers 2 and 3 that generate laser beams by exciting a laser active substance inside cores 2a and 3a by exciting light, propagate the laser beams inside the cores 2a and 3a, and output the laser beams from the end portions 2c and 3c, wherein the respective fiber lasers 2 and 3 have resonators 4 and 5 that reflect the laser beams on both ends 2b, 2c, 3b, and 3c thereof and have a structure in which a part of the cores 2a and 3a is reduced in diameter, the diameter reduced portions of the cores 2a and 3a are made proximal to each other, injection synchronization is carried out inside the resonators 4 and 5 by laser beams leaked from the cores 2a and 3a.

[Selected Drawing] Fig. 1







1/8

**Fig.1**


2/8

**Fig.2**



**3/8**




4/8

**Fig.4**


5/8

**Fig.5****Fig.6**

6/8

**Fig.7**

7/8

**Fig.8**

**Fig.9**